

ito

Terrestrial Digital Receiver



Standard Definition STBCIT6300

Advanced Features

- ◇ · MPEG-2 Digital & Fully DVB-T Compliant.
- ◇ · DTG & FreeView Compliant.
- ◇ · User-friendly EPG and Information Plate.
- ◇ · Max. 200 channels receivable.
- ◇ · Channel list mode in All, Favorite.
- ◇ · 5 Favorite channel groups (Max. 100 channels in a group).
- ◇ · Channel search in automatic, manual and network search.
- ◇ · Channel Sorting by channel number, Alphabet, FTA.
- ◇ · Dolby Digital Audio Output (Optical)
- ◇ · Parental control with block on system, all channels and programs by age limitation.
- ◇ · Timer Setting Supports automatic Turn-On and Off daily.
- ◇ · Auto language selection of program for Audio language with user setting in menu.
- ◇ · Subtitle decoding.
- ◇ · Software Upgrade via serial connection (RS-232)

IT Distribution International Pty Ltd
Unit 13, 78 Reserve Road, Artarmon, NSW 2064.
Phone: 02 99660066, Fax: 02 99660666,
Email: sales@itd.com.au, Web: www.itd.com.au

Ito is proudly represented, guaranteed and imported by
IT Distribution International Pty Ltd, ABN 47 093018378 (business established 1995)

Technical Specifications

Tuner

Input Frequency	UHF 470 MHz ~ 862 MHz VHF 174 MHz ~230 MHz
RF Input Level	-78dBm ~ -20dBm (75)
RF Input connector	IEC type Female
RF Output connector	IEC type Male
Nominal input impedance	75 ohm
Channel selection system	Electronic tuning, PLL
Step frequency	166.67KHz

Channel Decode

Demodulation	COFDM
--------------	-------

Video

Profile Level	MPEG-II <i>MP@ ML</i>
Output System	NTSC / PAL
Output Terminal	RCA, S-VIDEO
Output Level	1Vp-p (75) (RCA)

Audio

Audio Decoding	MPEG-II layer I & II
Freq response	20Hz ~ 20kHz
Output Terminal	Optical S/PDIF, RCA
Output Level	Adjustable (600 unbalance)

Working condition

Power supply voltage	AC: 90~240V 50/60 Hz
Power consumption	About 15W
Temperature	0°C ~ 40°C
Humidity	10% ~90%
Size	300 X 210 X 62mm(L/W/H)
Weight	Approx. 1.7Kg